

## TECHNICAL SHEET

25.05.2022 REV.0

### TRANSPARENT ANTIFOULING

#### DESCRIPTION AND CHARACTERISTICS

Transparent antifouling based on a copolymer which in the synthesis phase has been modified with some carefully selected biocides, free from copper.

<b>BINDER TYPE</b>	Modified acrylic copolymer
<b>COLOUR</b>	Colorless
<b>GLOSS LEVEL</b>	> 80 Gloss (60°)
<b>CAN PRESSURE</b>	From 4.2 to 4.8 Bar at 20 °C From 7.6 to 8.4 Bar at 50 °C
<b>DRYING TIME</b> (into air at 20 °C)	Dust free      30-40 min. Touch dry      2-3 hours
<b>OVERCOATING TIME</b>	8-12 hours minimum (20 °C)
<b>IMMISSION IN THE WATER</b>	24-48 hours minimum
<b>SPREADING CAPACITY</b>	From 0.7 to 1 m <sup>2</sup> for a 400 ml can.
<b>STORAGE</b>	Fresh and ventilated place.

#### USAGE

**Before use, carefully read the directions on the packaging and act accordingly.**

The surface of application must be perfectly clean, dry, degreased, and free from rust particles.

Before use shake well the can at last two minutes. Spraying covering layers at a distance of 25 cm.

#### N.B.

The above information covers at best our knowledge, but are not vinculating.

THE LABORATORY/SGQ